

Reinventing CSO Solutions

City of South Bend, Indiana

Intelligent Water Network Summit

Alexandria, Virginia


February 2018

Kieran Fahey
Environmental Scientist
Chartered Engineer




CITY OF SOUTH BEND
PUBLIC WORKS

South Bend, Indiana



Population:	101,516
Established:	1865
Treatment Plants:	1 (70MGal/day)
Outfalls:	35
CSO Overflow:	1-2 BGal/year
Abatement Plan:	\$860MM

LTCP Phase 2



Phase 2 is an exclusively grey infrastructure approach. Unfortunately no smart or green technology.


- 7 Storage tanks
- 1 Storage conduit
- 1 parallel interceptor

Residential Indicator across South Bend

RI 6-8%

RI > 8%

RI 4-6%




- MHI 35% below National Average
- 1 in 5 Residents over 10% of MHI

Per Capita Income \$19K

>20% residents make <\$15K


Phase 2 cost \$713m. That's \$10K for man, woman and child

#1 Turn on the lights




Most densely monitored Sewer System in the World
11,826,000 hours or 1,350 years of data


#2 Operate the Sewershed




#3 Modeling; the basis of any LTCP



#3 Old/Existing LTCP Model



#3 New Data Driven Model



Revising the LTCP- summary of previous slides

1. Data-driven maintenance created increased capacity;
2. Real Time Control exceeded expectations in reducing overflows;
3. New hyper-accurate model shows deficiencies in old LTCP model;
4. Original LTCP builds infrastructure but would not address the problem.

Novel South Bend Proposal:

We use our smart sewer data and new model to optimize the LTCP in the cloud!

Revising the LTCP: OptiSWMM


Previously we described how we came up with a better model- meaning, from a quality perspective, it was a better, more quality, product.

The next step regards the frequency of 'running' that new model.

Introducing OptiSWMM- allows us to run 1000s upon 1000s of model runs, not just a few scenarios like before. This allows many more permutations of LTCP alternatives to be considered.


LTCP update- how we were able to change

Sewer sensors + time = system knowledge

System knowledge  informing model with real data (CHRS data)


Real Data (CHRS data) + Optimization modelling x 10,000's runs (via OptiSWMM)

 Next Generation Data Driven alternative
Smarter Alternative for a Greener Alternative




**Plus Green
stormwater
Infrastructure**

Smart Infrastructure Results



SMART SEWER RESULTS WET WEATHER REDUCTION

Overflow Volume, MG Rain, IN



Cost of Compliance

Conditions	Typical Year Overflow (MG)	Reduction (MG)	Cost (MM)	Cost/Gal (\$/Gal)
Baseline (no improvements)	2,000			
Now	607	1,393 (all projects)	115	0.08
		462 (non-CSOnet)	105	0.23
		931 (only CSOnet)	10	0.01

Note: South Bend separated approximately 3K acres of its 13K acres of combined sewers. Non CSOnet-attributed CSO reductions estimated as Dec 17 of baseline overflow volume or 462MG.

Revising the LTCP: Optimization

Try every possible grey, green, and smart infrastructure option.

\$608 savings per household/year

